XLAB DELTA WING 200

USER INSTRUCTIONS AND IMPORTANT SAFETY INFORMATION

IMPORTANT: Please completely understand all user instructions and safety information before using this product.

TOOLS REQUIRED

4mm Allen wrench
8mm open-ended wrench

NOTE

The **GORILLA** cage comes loosely attached to the **DELTA WING** Mount with 22 mm long screws. This **DELTA WING** has a 3/8" black cylindrical spacer on the top screw and 1/4" black cylindrical spacer on the bottom screw. The spacers are to ensure that even with long saddles like the fi'zi:k that the water bottle will clear the rear of the saddle. There are also two silver 1/8" spacers beneath the locking nuts, to allow easy access to the nuts with an 8 mm wrench. The Mount is attached loosely to it's backplate with two 15 mm long screws with red Loctite on the threads that will help prevent the screws loosening once installed on the saddle.

INSTALLATION INSTRUCTIONS

The spacing of the rear saddle rails varies from each manufacturer. With some saddles it may be necessary to invert the Back Plate and have the narrowest part of the plate up under the saddle. This may allow easier access to the two threaded mounting holes. Using a 4 mm Allen wrench and an 8 mm wrench, fully tighten the two 22 mm long screws holding the cage to the Mount. Tighten to 30 in.lbs (3.4 nm) of torque. Next unscrew the two 15 mm screws from the backplate. Hold the Mount up to the back of the saddle rails and position the backplate inside the rails. Insert the two 15 mm screws through the Mount into the backplate. Hand-tighten and then check that the cage is in the position you require. Tighten to 30 in lbs (3.4 nm) of torque. DO NOT EXCEED THIS TORQUE. The Loctite on the threads will harden over 24 hours. You can still remove the screws in the future but the Loctite is a one-time use. You can purchase replacement screws with Loctite on the XLAB web store.
To add the recommended XLAB **X-STRIKE** CO_2 Inflation Kit between the cage and the black spacers, you will need to replace the two 22 mm screws with the two long 30 mm screws included with these instructions. Tighten to 30 in.lbs (3.4 nm) of torque.

MAINTENANCE

As with any high-tech racing gear, you need to routinely check for loose hardware, cracks or other damage and replace as required.

WARRANTY

1 Year warranty on Mount. Lifetime warranty on **GORILLA** cage. See website for details.

XLAB-USA.COM